

EL 846163293 US

TO WHOM IT MAY CONCERN, THE FOLLOWING IS A SPECIFICATION OF THE  
AFORESAID INVENTION

09966738-092801

1 A PROPRIETARY PROTOCOL FOR A SYSTEM  
2 CONTROLLER FOR CONTROLLING DEVICE CONTROLLERS ON  
3 A NETWORK HAVING AN OPEN COMMUNICATION PROTOCOL

BACKGROUND

4 The present invention generally relates to a communication protocol used  
5 in system controllers for network control systems, and more particularly to a protocol for  
6 a system controller for controlling a control system having a network with an open  
7 communication protocol.

8 It is known in the control systems industry, especially the building control  
9 systems, to employ a control network to allow various system components to  
10 communicate with each other. Until recently, communication between the components  
11 in the network was handled through proprietary protocols developed by the control  
12 network developers/manufacturers. Increasingly, however, the control networks are  
13 now being implemented with open communication standards such as LonTalk® and  
14 BACnet. These communication protocols permit system components that are produced  
15 by different manufactures to communicate with each other, thus providing the network  
16 designers the flexibility to choose system components from various sources.

17 Known control systems typically include one or more system controllers  
18 that are connected via a control network to device controllers that operatively control  
19 network devices. The system controllers typically transmit commands to the device  
20 controllers for operating the network devices, and also receive data from the device  
21 controllers regarding status and other information about the network devices that may  
22 be of interest to the system controller for making decisions.

23 A problem associated with the known control system arrangements is that  
24 the communication between the system controller and the device controllers must be  
25 conducted via the open protocol of the system network. These protocols do not always  
26 have the capacity to provide the support necessary for implementing complex and  
27 increased functionalities required by some control systems, such as a  
28 Heating/Ventilation/Air Conditioning (HVAC) system, for example. The known control  
29 system arrangements also limit designers' creativity in solving problems or expanding  
30 the capabilities of the system controller, because the designers are confined to the

1 protocol of and the type of data provided by the network in place. Addition of new  
2 control applications to the control system is also complicated for the same reasons.

### 3 SUMMARY OF THE INVENTION

4 The present invention is directed a communication protocol which is  
5 employed in a system controller for controlling device controllers in a control system that  
6 is built around a network utilizing a network specific communication data format and  
7 protocol. The present proprietary protocol is adapted to be embedded in the network  
8 protocol and carry proprietary data between an application controller and various  
9 applications of the system controller.

### 10 BRIEF DESCRIPTION OF THE DRAWINGS

11 FIGURE 1 is a logical block diagram of a system controller that uses the  
12 present communication protocol;

13 FIG. 2 is block diagram of the system controller of FIG. 1 shown  
14 incorporated into a control network;

15 FIG. 3 is a logical block diagram illustrating the types of communication  
16 protocols that may be employed in the control network;

17 FIG. 4 is an illustration of the data fields associated with a single system  
18 point (SP) data format;

19 FIG. 5 is a simplified illustration of various fields that are selectively  
20 provided in the system point protocol messages of the present invention;

21 FIG. 6 is an illustration of a notification field in some of the present system  
22 point protocol messages;

23 FIG. 7 is a system point protocol message format for a  
24 MSG\_ID\_SP\_DISCOVER\_PUID message;

25 FIG. 8 is a system point protocol message format for a  
26 MSG\_ID\_SP\_DISCOVER\_NAME message;

27 FIG. 9 is a system point protocol message format for a  
28 MSG\_ID\_SP\_SUBSCRIBE\_EL message;

29 FIG. 10 is a system point protocol message format for a MSG\_ID\_SP\_  
30 UNSUBSCRIBE\_EL message;

FIG. 11 is a system point protocol message format for a MSG\_ID\_SP\_UNSUBSCRIBE\_ALL\_EL message;

FIG. 12 is a system point protocol message format for a MSG\_ID\_SP\_OVERRIDE\_WRITE\_SP message;

FIG. 13 is a system point protocol message format for a MSG\_ID\_SP\_RELEASE message;

FIG. 14 is a system point protocol message format for a MSG\_ID\_SP\_VAL\_QUERY message;

FIG. 15 is a system point protocol message format for a MSG\_ID\_SP\_QUAL\_QUERY message;

FIG. 16 is a system point protocol message format for a MSG\_ID\_SP\_NODE\_QUERY message;

FIG. 17 is a system point protocol message format for a MSG\_ID\_SP\_CANCEL\_TRANSACTION message;

FIG. 18 is a system point protocol message format for a MSG\_ID\_SP\_SUBSCRIBE\_EVENT message;

FIG. 19 is a system point protocol message format for a MSG\_ID\_SP\_UNSUBSCRIBE\_EVENT message;

FIG. 20 is a system point protocol message format for a MSG\_ID\_SP\_RESYNC message;

FIG. 21 is a system point protocol message format for a MSG\_ID\_SP\_EVENT\_RPT message;

FIG. 22 is a system point protocol message format for a MSG\_ID\_SP\_DISCOVERED message;

FIG. 23 is a system point protocol message format for a MSG\_ID\_SP\_VAL\_RPT message;

FIG. 24 is an alternative system point protocol message format for the MSG\_ID\_SP\_VAL\_RPT message of FIG. 23;

FIG. 25 is a system point protocol message format for a MSG\_ID\_SP\_QUAL\_RPT message;

FIG. 26 is an alternate system point protocol message format for the MSG\_ID\_SP\_QUAL\_RPT message of FIG. 25;

FIG. 27 is a system point protocol message format for a MSG\_ID\_SP\_EVENT\_RPT message; and,

FIG. 28 is a system point protocol message format for a MSG\_ID\_APPLICATION\_ERROR message.

#### DETAILED DESCRIPTION

Broadly stated, the present invention is directed to a proprietary communication protocol used in a system controller that includes an application controller and a plurality of applications for controlling a plurality of device controllers on a control network by using data relating to system points that correspond to data variables in the network. The protocol communicates a plurality of predefined messages between the application controller and the applications for instructing the application controller to perform a function relating to a select system point, and for reporting to the applications in response to the instructions. The protocol includes a message identification field for identifying a select message from the plurality of messages, and a protocol identification field for identifying the select message as being transmitted via the proprietary communication protocol.

In accordance with another aspect of the present invention, a proprietary communication protocol is used in a system controller that includes an application controller and a plurality of applications for controlling a plurality of device controllers on a control network by using data relating to system points that correspond to data variables in the network. The protocol communicates a plurality of predefined messages between the application controller and the applications for instructing the application controller to report events that occur in the applications and the device controllers, and for reporting to the applications in response to the instructions. The protocol includes a message identification field for identifying a select message from the plurality of messages, and a protocol identification field for identifying the select message as being transmitted via the proprietary communication protocol.

Turning now to FIG. 1, a system controller in which the present communication protocol is used to transmit data is indicated generally at 100 and includes a plurality of applications 102, which are in communication with a network point record application (NPRA) 104. A system variable (SV) server 106 is connected

1 between the NPRA 104 and a control network 108 and serves as an interface between  
2 the NPRA 104 and the network data flow. It should be noted that FIG. 1 is a logical data  
3 flow view of the system controller 100 and that the SV server 106 and the applications  
4 102 may reside at different locations along the network 108 from that of the NPRA 104.  
5 The NPRA 104 and the applications 102 may communicate directly, bypassing the SV  
6 server 106, or via the network through the SV server 106.

7 As shown in FIG. 2, a control system 110 includes a plurality of device  
8 controllers that are network 108 compliant. They include application specific controllers  
9 (ASC) 112 (two shown) for controlling a number of physical devices 114, for example, a  
10 variable air volume (VAV) box that controls a fan for blowing hot or cold air into an area.  
11 Also included are a number of programmable equipment controllers (PEC) 116 (one  
12 shown), which also control physical devices 114 in the control system 110. In addition,  
13 the PECs 116 include features for enabling more sophisticated control processes, and  
14 generate data necessary for producing system reports. A workstation (WS) 118 allows  
15 a user of the control system 110 to input instructions to the device controllers 112, 116  
16 for controlling the physical network devices 114, and gain access to the system data  
17 necessary for making decisions regarding the operation of the control system 110.

18 The WS 118, in the preferred embodiment, includes an internet interface  
19 119 which allows the WS to be interfaced with the internet 121. A connection to the  
20 internet can be through an ethernet card or through a modem. Alternatively, an internet  
21 interface 119 can be provided in one of the PECs 116, in which case the connection  
22 mechanism to the internet 121 would be hard coded into the PEC instead of using an  
23 ethernet card. In this manner, the operation of the control system 110 can be controlled  
24 remotely through the internet 121.

25 The applications 102 may be a part of the workstation 118 used to  
26 subscribe for changes in the status of the network devices 114, for example. They  
27 might also be a part of the PEC 116, such as an alarm detector for detecting and  
28 reporting alarm conditions to an operator, or a totalization application for totalizing and  
29 calculating power used by the network devices 114, or for calculating the total ON time  
30 for a device such as a fan. The NPRA 104 provides a means of data collection,  
31 translation, reporting, and updating from data sources on the network 108. The SV  
32 servers 106 facilitate transmission of data or system variables (SVs) from the device  
33 controllers 112, 116 to the NPRA 104, and data from the NPRA to the device

1 controllers. The term system variables (SV) is defined to be values or data associated  
2 with the network devices 114 that are transmitted through the network via the network  
3 communication protocol, e.g., voltage from a sensor, a temperature reading, etc.

4 As shown in FIG. 2, the system controller 100 is provided in the PEC 116  
5 or the workstation 118, but it may also be provided independently in a stand-alone unit.  
6 Each system controller 100 includes one NPRA 104, a plurality of applications 102 and  
7 one or more SV servers 106 which are incorporated into the device controllers 112, 116.  
8 Each ASC and PEC 112, 116 represents a "node" in the network 108, which is a logical  
9 location of the SV server 106. While only one system controller 100 is shown in FIG. 2,  
10 it should be understood that more than one system controller may be provided in the  
11 control system 110, where each system controller would be responsible for operatively  
12 communicating with its designated nodes.

13 Turning now to FIG. 3, communication between the device controllers 112,  
14 116 is through a protocol 120 that is specific to the network 108 on which the system  
15 controller 100 is connected, such as for example, LonTalk® in a LON network. Data or  
16 system variables (SVs) that are transmitted between the SV servers 106 and the device  
17 controllers 112, 116 are in the format defined by the network protocol 120. Between the  
18 SV servers 106 and the NPRA 104, the format of the data being transmitted is the same  
19 as at the network level. Accordingly, the mechanism of the protocol 120 of the network  
20 108 may be utilized in transmitting data, either through the local SV server 106 or  
21 directly between the NPRA 104 and the SV servers 106 in the other device controllers  
22 112, 116 in the network 108.

23 A proprietary communication protocol 122 may also be used to transmit  
24 data between the NPRA 104 and the SV servers 106, so as to provide a layer of  
25 abstraction between the network 108 and the NPRA. In other words, the proprietary  
26 protocol 122 used between the SV servers 106 and the NPRA 104 would further isolate  
27 the system controller 100 from the network 108, so that the system controller is not  
28 bound to one particular control network. The proprietary protocol 122 at this level would  
29 also allow the system controller designers to implement additional capabilities in  
30 manipulating data or system variables. One example of the proprietary protocol 122 for  
31 implementing between the NPRA 104 and the SV servers 106 is described in detail in a  
32 commonly assigned patent application entitle PROPRIETARY PROTOCOL FOR

1 COMMUNICATING NETWORK VARIABLES ON A CONTROL NETWORK, filed  
2 simultaneously herewith.

3 In accordance with the present invention, a "system point" (SP) is  
4 assigned for each system variable (SV) on the network 108 and other network data not  
5 associated with system variables. A system point might represent a room temperature  
6 or a room temperature setpoint measured or set by a thermostat (which would be a  
7 network device 114 shown in FIG. 2), for example. Each SP has associated dynamic  
8 and static information that are organized into various data fields. When the system  
9 variables (SV) from the SV server 106 are received, the NPRA 104 converts or maps  
10 the SVs into corresponding SPs.

11 In accordance with the present invention, data relating to the SPs are  
12 communicated between the NPRA 104 and the applications 102 via a system point (SP)  
13 protocol 124. The SP protocol is preferably embedded into the network protocol 120 of  
14 the network 108. In the LONTalk® protocol, for example, the SP protocol would be  
15 incorporated into the "explicit messages" fields specifically designated for incorporation  
16 of proprietary communication messages.

17 Turning now to FIG. 4, a single SP 126 is shown and includes a plurality of  
18 fields which describe the characteristics of the SP. The fields of the SP 126 are  
19 described in TABLE 1 below (the number next to the field name corresponds to the  
20 reference numerals of FIG. 4).

Field Name	Type	S/D	Description
Name 126	Array of 36 U08's	S	User defined SP name.
PUID 128	U32	S	Unique ID number for the SP.
VID 130	U32	S	Unique ID number for the SV associated with the SP. This field will be undefined if the SP is not associated with a SV.
SVAddress 132	U32	S	The logical address of the SV associated with the SP
Over Enable 134	U08	S	Indicates whether the SP can be overridden.
SVT 136	U16	S	The system variable type associated with the SP.
Writable 138	U08	S	This field defines if the SV corresponding to the SP can be written to.
DefPollCycle 140	R32	S	Default polling cycle for the SV associated with the SP.



Field Name	Type	S/D	Description
PwrFailAct 142	U08	S	This field is valid on writeable points only. Describes the action that the NPRA 104 will take when the NPRA is powered-on.
Quality 144	U16	D	This field provides the quality of the SP's value to indicate the condition of the SV associated with the SP.
WrtPriority 146	U08	D	The current write priority value of the SP.
Ovrd Priority 148	U08	D	The current override priority value of the SP.
Element Number 150	U08	S	The identification number or index of the SP element.
SPT 152	U16	S	The type of the system point (engineering units).
Def COV Limit 154	R32	S	Default change of value limit for the SP element.
SP Numeric Value 156	Array of up to 32 R32's	D	The current numeric value of an SP element in system point type (SPT) units.
SP String Value 158	Array of 32 U08's	D	The current string value of an SP element in SPT unit.
User Defined 160	User defined	D/S	Additional field for use in specific applications.

TABLE 1

The column named "Type" indicates the preferred number of bytes reserved for the corresponding fields of the SP. The first letter indicates whether the value is signed (S), unsigned (U) or a real number (R), and the following two numerals indicate the number of bits in the field. For example, the type "U08" represents an unsigned number having 8 bits (i.e., 0 to 255), and the type "S08" represents a signed number having 8 bits (i.e., -128 to +127). The S/D column indicates whether the field is static or dynamic. The static fields are not modified, while the dynamic fields may be modified. The SPs include one or more SP "elements," each of which is, in effect, an independent variable with an associated dynamic value. For example, one element of the SP could contain a state, while another element could contain the time until that state occurs.

Turning now to FIG. 5, and in accordance with the present invention, the system point (SP) protocol 124 includes a number of common fields, one or more of which are selectively incorporated into different messages. These fields include a protocol identification (ID) field 162 and a message ID field 164. In the preferred

1 embodiment, the protocol ID field 162 is set to PROT\_ID\_SP, which is an unsigned one  
2 byte value, i.e., a U08 value, for all SP protocol messages. The message ID field 164  
3 identifies the type of message that is sent from the clients 102 to the NPRA 104, or from  
4 the NPRA to the clients.

5 An SP override/write command priority field 166 is preferably a one-byte  
6 field that holds the values that define the priority levels of the messages that are used to  
7 command writing or overriding of the SPs. The term "writing" is defined to mean  
8 updating of the SP value, and "override" is defined to mean updating of the existing SP  
9 values and also preventing other clients 102 from changing the overridden value. The  
10 priority levels prevent low priority clients 102 from overwriting or re-overriding the SP  
11 values set by high priority NPRA clients.

12 A transaction ID field 168, which is a four-byte field in the preferred  
13 embodiment, carries values representing the transaction ID of a message sent by the  
14 client 102 to the NPRA 104. The same transaction ID is then used in a response  
15 message or report from the NPRA 104 to the client 102. In this manner, the messages  
16 sent by the client 102 are readily identified with their corresponding responses from the  
17 NPRA 104. In the preferred embodiment, the client 102 uses a new and unique  
18 transaction ID each time it sends an SP protocol message.

19 An event ID field 170 holds a value that identifies the type of event that is  
20 being subscribed for by the clients 102 from the NPRA 104. The event ID field 170 is  
21 also employed when the NPRA 104 reports on events that have occurred in the control  
22 system 110, for example, a node failure or a return from a node failure. A last message  
23 flag field 172 holds a value that indicates that a response message from the NPRA 104  
24 to the clients 102 is the last in the series of response messages. In the preferred  
25 embodiment, the NPRA 104 sets the last message flag field equal to "1" within the last  
26 message associated with a particular transaction. In all preceding messages the flag  
27 field 172 is set to "0".

28 An SP element field 174 carries the values of the two different classes of  
29 the SP elements, which are string elements and numeric elements. The string elements  
30 are preferably limited to 31 characters in length, and therefore, will have up thirty-one  
31 U08 values stored in an array. The numeric element values in the preferred  
32 embodiment are expressed as an array of 1 to 31 32-bit floating values (i.e. R32's).

An element format field 176 indicates the format that the SP elements are to be conveyed. In the preferred embodiment, the messages designated as "format 0" convey only the value of the elements (such as for display on a Workstation 118 application 102, while those designated as "format 1" are conveyed with units and formatting information so that the elements can be displayed on a portable (typically hand-held) device application 102. For numeric elements, these messages convey the system point type (SPT), formatting information (such as the element's units and the number of digits right of the decimal point), as well as the value of the numeric elements. For string elements, these messages convey the string length and the variable length character array that contains the contents of the string.

A notification field 178 is provided for setting flags that are used to individually enable, disable or indicate specific notifications relating to particular characteristics of the SPs. This is a single byte field that is bit-mapped as shown in FIG. 6. For example, bit 0 of the field might be used for setting a "change of value" (COV) notification flag for changes in the value of a particular SP, and bit 1 of the field might be used for setting a "change of quality" (COQ) notification flag for changes in the quality of an SP, etc. While the notification field 178 is depicted in FIG. 6 as having four bits, more or less bits may be designated for this field as necessary for notifying purposes. A date/time field 180 is also included in the SP protocol for conveying the date and the time values of an event that occurs in the control system 110. This field preferably holds a 64-bit floating (i.e., R64) value.

The following predefined message types are sent from the clients 102 to the NPRA 104 and selectively include some of the fields shown in FIG. 5:

<u>MESSAGE TYPE</u>	<u>MESSAGE ID</u>
Discover SP by PUID (unique system point ID)	MSG_ID_SP_DISCOVER_PUID
Discover SP by Name	MSG_ID_SP_DISCOVER_NAME
Subscribe Element	MSG_ID_SP_SUBSCRIBE_EL
Unsubscribe Element	MSG_ID_SP_UNSUBSCRIBE_EL
Unsubscribe All Elements	MSG_ID_SP_UNSUBSCRIBE_ALL_EL
Override/Write SP	MSG_ID_SP_OVERRIDE_WRITE_SP
Release	MSG_ID_SP_RELEASE
Value/Quality Query	MSG_ID_SP_VAL_QUERY
Quality Query	MSG_ID_SP_QUAL_QUERY
Node Query	MSG_ID_SP_NODE_QUERY
Cancel Transaction	MSG_ID_SP_CANCEL_TRANSACTION
Subscribe Event	MSG_ID_SP_SUBSCRIBE_EVENT
Unsubscribe Event	MSG_ID_SP_UNSUBSCRIBE_EVENT

1	Subscribe All COS	MSG_ID_SP_SUBSCRIBE_ALL_COS
2	Unsubscribe All COS	MSG_ID_SP_UNSUBSCRIBE_ALL_COS
3	Set Totalized Value	MSG_ID_SP_SET_TOTALIZED_VALUE
4	Resync	MSG_ID_SP_RESYNC
5	Event Report	MSG_ID_SP_EVENT_RPT

6 The following predefined message types are sent from the NPRA 104 to the clients 102  
7 and selectively include some of the fields shown in FIG. 5:

8	<u>MESSAGE TYPE</u>	<u>MESSAGE ID</u>
9	SP Discovered	MSG_ID_SP_DISCOVERED
10	Value/Quality Report (format 0)	MSG_ID_SP_VAL_RPT_0
11	Value/Quality Report (format 1)	MSG_ID_SP_VAL_RPT_1
12	Quality Report (format 0)	MSG_ID_SP_QUAL_RPT_0
13	Quality Report (format 1)	MSG_ID_SP_QUAL_RPT
14	Event Report	MSG_ID_SP_EVENT_RPT
15	Command NAK	MSG_ID_APPLICATION_ERROR

16 It should be noted that each message field is “serialized”, i.e. its bytes are  
17 stored in a predefined order. The preferable order is big endian, or the storing the most  
18 significant byte (MSB) of the field first.

19 Each SP point in the NPRA 104 is assigned a unique identification (PUID)  
20 number. A MSG\_ID\_SP\_DISCOVER\_PUID message is broadcast from a client 102 to  
21 the NPRA 104 to discover if the NPRA has a specified SP within its database. The  
22 PUID number is stored in the PUID field 128 of each SP (best shown in FIG. 4). The  
23 NPRA 104 receiving this message responds by sending an  
24 “MSG\_ID\_SP\_DISCOVERED” message (discussed below) containing the same  
25 TRANSACTION ID (as the MSG\_ID\_SP\_DISCOVER\_PUID message) to the client 102,  
26 if the SP with the specified PUID number is found in the SP database. The serialized  
27 format of the MSG\_ID\_SP\_DISCOVER\_PUID message in accordance with the SP  
28 protocol is shown in FIG. 7, including the protocol ID field 162, the message field 164,  
29 the transaction ID field 168 (shown in FIG. 5). In addition, the  
30 MSG\_ID\_SP\_DISCOVER\_PUID message also includes a PUID field for identifying the  
31 PUID number of the SP stored in the database of the NPRA 104.

32 A MSG\_ID\_SP\_DISCOVER\_NAME message is sent from the client 102 to  
33 the NPRA 104 to discover if a particular SP is stored within its database, as specified by  
34 the SP’s unique text name. The NPRA 104 responds to this message by sending an

1 "MSG\_ID\_SP\_DISCOVERED" message (discussed below) containing the same  
2 TRANSACTION ID (as the MSG\_ID\_SP\_DISCOVER\_PUID message) to the client 102,  
3 if the SP is found in the SP database that matches the unique text name. The serialized  
4 format of the MSG\_ID\_SP\_DISCOVER\_NAME message in accordance with the SP  
5 protocol is shown in FIG. 8, including the NAME field indicating the text name of the SP.

6 Turning to FIG. 9, a MSG\_ID\_SP\_SUBSCRIBE\_EL message is sent from  
7 the clients 102 to the NPRA 104 to subscribe for changes in (value, state, quality, etc.)  
8 or periodic reporting of a specified element within selected SPs. This message may  
9 also be used to subscribe for changes in or periodic reporting of other characteristics of  
10 the SPs besides the SP elements.

11 In addition to the message fields described above in connection with the  
12 other SP protocol messages, the MSG\_ID\_SP\_SUBSCRIBE\_EL message includes an  
13 SP ELEMENT INDEX field that specifies the element within the SP for which the client  
14 102 wishes to subscribe. The SPs include up to 31 elements having values which  
15 change independently.

16 A NOTIFICATION field is provided for setting flags in the bit fields that are  
17 used to individually enable specific notifications (for example, change of value (COV),  
18 change of quality (COQ), change of state (COS), change of totalization (COT)) that the  
19 client is interested in subscribing. A SYNC/UNSYNC POLLING bit in the  
20 NOTIFICATION field is reserved for each type of notifications that are set. A "0" in this  
21 bit field instructs the NPRA 104 to poll for the specified notifications when the  
22 subscription (i.e., the MSG\_ID\_SP\_SUBSCRIBE\_EL message) is received, at the  
23 specified interval as indicated in a COV LIMIT/POLL RATE field set aside for this  
24 purpose. A "1" in this bit instructs the NPRA 104 to poll at the specified interval set in  
25 the COV LIMIT/POLL RATE field, but starting only after a predetermined time, i.e., the  
26 start of polling is synchronized with a time boundary, as specified in a POLL SYNC  
27 TIME field. It should be understood that the POLL SYNC TIME field is only used in the  
28 message if the SYNC/UNSYNC POLLING bit is set to "1." Otherwise, this field is not  
29 used in the message.

30 A "0" (ALL) in an ANY/ALL bit of the NOTIFICATION field indicates that all  
31 of the (COV, COQ, COS, COT) notifications enabled by the user in the message must  
32 be supported by the SP in the NPRA 104. If the SP does not support any one of the

selected notifications, then the message will not be accepted. A "1" (ANY) indicates that any of the notifications (COV, COQ, COS, COT) enabled by the user and which the SP supports should be applied to the SP at the NPRA 104. The message will be accepted even if the SP does not support all the notifications enabled in the message.

A POLLING/COV bit of the NOTIFICATION field determines whether the enabled notifications should be reported based on polling or when the value of the SP element changes. A USE\_DEFAULT bit indicates (if the POLLING/COV bit is set to polling) whether the notification report should be based on the value change limit specified in the COV LIMIT/POLL RATE field of the message or the predefined default limit set in the database of the NPRA 104. It should be noted that the COV LIMIT/POLL RATE field contains either the value change limit or the desired polling rate. A REPORT FORMAT field is used to select a predetermined report format for receiving the reports from the NPRA 104.

Turning to FIG. 10, a MSG\_ID\_SP\_UNSUBSCRIBE\_EL message is sent from the client 102 to the NPRA 104 to cancel the subscription set by the MSG\_ID\_SUBSCRIBE\_EL message. In addition to some of the fields discussed with respect to the MSG\_ID\_SP\_SUBSCRIBE\_EL, the MSG\_ID\_SP\_UNSUBSCRIBE\_EL message indicates a DISABLE field for specifying the type of notifications (e.g., COV, COQ, COS, and/or COT notifications) to unsubscribe.

Turning to FIG. 11, a MSG\_ID\_SP\_UNSUBSCRIBE\_ALL\_EL message is sent from the client 102 to the NPRA 104 to unsubscribe all notifications (COV, COP, COQ, COS, COT) on all SP elements on all SPs that the client 102 is currently subscribed to. This message is typically be sent at shutdown and start-up by the client 102 (such as the workstation 118) to remove any remaining subscriptions.

Turning to FIG. 12, a MSG\_ID\_SP\_OVERRIDE\_WRITE\_SP message is sent from the client 102 to the NPRA 104 to override or write new values to all elements within an SP. In addition to the fields described above in connection with the other SP protocol messages, this message includes a single-byte OVERRIDE/WRITE field including a bit (bit 7) for indicating the type of operation that is desired, i.e., whether override or write, and remaining bits (OVERRIDE/WRITE PRIORITY) indicating the priority of the message. The message will only be accepted by the NPRA 104 if the specified priority is greater than or equal to the current priority for the SP, as indicated in

fields 146, 148 of the SP (shown in FIG. 4). If the specified priority is below that of the current priority, a negative acknowledgement (NAK) is returned to the client 102 that sent the message.

In addition to the common fields described above in connection with the other SP protocol messages, the MSG\_ID\_SP\_OVERRIDE\_WRITE\_SP message includes an OPERATOR ID field which indicates the identity of a user who is responsible for sending the message. An SPF field indicates the total number of elements that are in the SP, and the ELEMENT VALUE fields hold the value of those elements to be overridden or written. In the preferred embodiment, the message only supports numeric element and not string elements. Element values are conveyed as a 32-bit floating point number (i.e. an R32 number), and accordingly require 4 bytes for each value, which are arranged from the most significant byte (MSB) to the least significant byte (LSB), as shown in FIG 12.

Turning to FIG. 13, a MSG\_ID\_SP\_RELEASE message is sent from the client 102 to the NPRA 104 to release an SP from an override or write restriction so that other lower priority clients 102 are allowed to override or write to the SP. The effect of the release is to clear the priority of the SP. It should be noted that any client 102 can send this message, and not just the one that set the override or write of the SP. However, the message will only be accepted if the priority of the client 102 is greater than or equal to the current priority for the SP. Otherwise, a NAK is returned to the client 102. In addition to the common fields described above in connection with the other messages, this message includes a single byte OVERRIDE/WRITE field including a bit (bit 7) for identifying the type of release, i.e., whether the release is for an override or a write. The remaining bits of this field (OVERRIDE/WRITE PRIORITY) indicates the priority of the message so that the NPRA 104 is able to determine whether the message can be accepted.

A MSG\_ID\_SP\_XX\_QUERY message is sent from the client 102 to the NPRA 104 to request a report on one or more SPs that currently have a particular data which is of interest to the client 102 sending the message. For example, a MSG\_ID\_SP\_VAL\_QUERY message, as depicted in in FIG. 14, is sent to request a report on an SP or on all the SPs that current have a write priority that is greater than or equal to the specified minimum write priority, and an override priority that is greater than or equal to the specified minimum override priority. Accordingly, in addition to

1 the common fields described above, the MSG\_ID\_SP\_VAL\_QUERY message includes  
2 MIN WRITE PRIORITY and MIN OVERRIDE PRIORITY fields.

3 Turning to FIG. 15, a MSG\_ID\_SP\_QUAL\_QUERY message is sent from  
4 the client 102 to the NPRA 104 to request a report on one or more SPs that conform to  
5 the specified quality mask, which indicates whether the source of the data is operational.  
6 An example of an SP having a bad quality would be an SP that corresponds to a system  
7 variable (SV) which originated from a network device 114 or the device controllers 112,  
8 116 (shown in FIG. 2) that has experienced a failure.

9 Turning to FIG. 16, a MSG\_ID\_SP\_NODE\_QUERY message is sent from  
10 the client 102 to the NPRA 104 to instruct the NPRA to immediately schedule a node for  
11 interrogation to determine if that node has failed or is operational, rather than waiting for  
12 the scheduled next scan by the NPRA. In addition to the common fields described  
13 above in connection with the other messages, the MSG\_ID\_SP\_NODE\_QUERY  
14 message includes a SUBNET ID field and a NODE ID field which identify the logical  
15 network address of the node being queried.

16 Turning to FIG. 17, the MSG\_ID\_SP\_CANCEL\_TRANSACTION message is  
17 sent from the client 102 to the NPRA 104 to cancel a previously sent  
18 MSG\_ID\_SP\_XX\_QUERY message. The transaction to be cancelled is specified by the  
19 TRANSACTION ID field.

20 Turning to FIG. 18, the MSG\_ID\_SP\_SUBSCRIBE\_EVENT message is  
21 sent from the client 102 to the NPRA 104 to subscribe for event notifications. The term  
22 "event" is defined to mean general error conditions in the applications (clients) 102 in  
23 the control system 110. The message includes a MINIMUM EVENT SEVERITY field  
24 that instructs the NPRA 104 to only report events that have a predefined severity level  
25 that is higher than the level indicated in this field. An APPLICATION ID field identifies  
26 the applications (clients) 102 for which the event notification is desired.

27 A MSG\_ID\_SP\_UNSUBSCRIBE\_EVENT message is sent from the client  
28 102 to the NPRA 104 to unsubscribe for the event notifications described above. The  
29 SP protocol for this message is shown in FIG. 19.

30 Turning to FIG. 20, a MSG\_ID\_SP\_RESYNC message is sent from the  
31 client 102 to the NPRA 104 to instruct the NPRA to resynchronize or query all of the SV  
32 servers 106 operatively connected to the NPRA to determine which SVs are currently  
33 overridden, and then update the NPRA database with the results of these queries.



Turning to FIG. 21, a MSG\_ID\_SP\_EVENT\_RPT message is sent from the client 102 (or the NPRA 104 itself) to the NPRA 104 to report the occurrence of an event detected by the client, such as a node failure event or node return-from failure event detected by a NPRA. In addition to the common fields described above, the MSG\_ID\_SP\_EVENT\_RPT message includes an EVENT ID field indicating the type of predefined event that has occurred. The events have a predefined severity level, and those events that have severity level above the minimum level indicated in the EVENT SEVERITY field are reported to the NPRA 104. An EVENT TIME STAMP field is provided in the message to record the time of the event. The MSG\_ID\_SP\_EVENT\_RPT message further includes an ARG LENGTH field that indicates the number of bytes that are in an ARGUMENT field, which provides the detailed information about the event that is being reported.

Turning to FIG. 22, a MSG\_ID\_SP\_DISCOVERED message is sent from the NPRA 104 to a client 102 in response to a command from the client to discover SP by its point unique ID (PUID) number or its name (MSG\_ID\_SP\_DISCOVER\_PUID and MSG\_ID\_SP\_DISCOVER\_NAME messages shown in FIGS. 7 and 8) discussed above, if the specified SP was found within the database of the NPRA. This message includes, in addition to the common fields described above, a LAST MESSAGE field for indicating whether this message is the last message associated with the transaction identified in the TRANSACTION ID field.

Turning to FIG. 23, a MSG\_ID\_SP\_VAL\_RPT message is sent from the NPRA 104 to the clients 102 in response to requests from the clients for reports on the SPs for data of interest. In the preferred embodiment, this message is used to report the occurrence of a change of value (COV) and/or change of quality (COQ) for the specified SP and of a change of priority (COP) of the write priority and/or override priority for the specified SP. This message is used also in response to the MSG\_ID\_SP\_SUBSCRIBE\_EL message (shown in FIG. 9), for subscribing for an element of the SP, and in response to a request for a report on an SP that has a write priority that is greater than or equal to a specified minimum write priority and an override priority that is greater than or equal to the specified minimum override priority, i.e., the MSG\_ID\_SP\_VAL\_QUERY message (shown in FIG. 14) discussed above.

As seen in FIG. 23, the MSG\_ID\_SP\_VAL\_RPT message includes, in addition to the common fields discussed above in connection with the other messages,

1 a NOTIFICATION field that has bit flags to indicate a change of value (COV) and a  
2 change of quality (COQ), if this message is sent as a COV/COQ notification report. If  
3 this message is sent in response to a query messages (the MSG\_ID\_SP\_XX\_QUERY  
4 messages shown in FIGS. 14-16), then the flags are cleared. A QUALITY field indicates  
5 the current quality level of the data source, which is needed if this report is in response  
6 to a query regarding quality, i.e., the MSG\_ID\_SP\_QUAL\_QUERY message (shown in  
7 FIG. 15). SP WRITE PRIORITY and the SP OVERRIDE PRIORITY fields convey the  
8 current write and override priority of the SP. The SPF field indicates the number of SP  
9 elements that are in the specified SP.

10 It should be noted that the report format of the MSG\_ID\_SP\_VAL\_RPT  
11 may be modified to provide the information specified by the requesting client 102. An  
12 example of an alternate format for reporting the MSG\_ID\_SP\_VAL\_RPT message is  
13 shown in FIG. 24, which in addition to the fields shown in FIG. 23, further includes a  
14 NAME field for providing the name of the specified SP, if this information is requested by  
15 the client 102.

16 Turning to FIG. 25, a MSG\_ID\_SP\_QUAL\_RPT message is sent from the  
17 NPRA 104 to the client 102 in response to the MSG\_ID\_SP\_QUAL\_QUERY message  
18 (shown in FIG. 15) or the MSG\_ID\_SP\_SUBSCRIBE\_EL message (shown in FIG. 9)  
19 with the COQ notification bit specified. In addition to the common fields described  
20 above in connection with the other messages, a QUALITY field indicates the predefined  
21 level of quality associated with the specified SP. The report format may be modified to  
22 provide the information specified by the requesting client 102. An example of an  
23 alternate format for reporting the MSG\_ID\_SP\_QUAL\_RPT message is shown in FIG.  
24 26, which in addition to the fields shown in FIG. 25, further includes a NAME field for  
25 providing the name of the specified SP, if this information is requested by the client 102.

26 Turning to FIG. 27, a MSG\_ID\_SP\_EVENT\_RPT message is sent from  
27 the NPRA 104 to the client 102 to report the occurrence of the events specified by the  
28 client. In addition to the common fields described above in connection with the other  
29 messages, this message further includes ORIGINATOR SUBNET ID and ORIGINATOR  
30 NODE ID fields for identifying the logical network address of the node of the application  
31 (i.e., the client) 102 that has experienced the subscribed event. An APPLICATION ID  
32 FIELD identifies the application 102 that has detected the event. An EVENT ID field  
33 identifies the type of event that has occurred at the application 102, and an EVENT

1 SEVERITY field indicates the level of severity of the event, which is predetermined for  
2 each event. An EVENT TIME STAMP shows the time at which the event has occurred,  
3 and an ARG LENGTH field indicates the number of bytes (in the ARG field) that are  
4 used to provide detailed information (argument) regarding the event.

5 Turning to FIG. 28, a MSG\_ID\_APPLICATION\_ERROR message is sent  
6 from the NPRA 104 to the client 102 report that the NPRA was unable to execute the  
7 specified command from the client. A MODULE field indicates the software module  
8 where the error occurred, while an ERROR code field indicates the type of error that  
9 occurred (i.e., the reason why the NPRA 104 could not execute the command  
10 message). An ORIGINAL MESSAGE field contains the original command message that  
11 the NPRA 104 was unable to execute.

12 From the foregoing description, it should be understood that an improved  
13 protocol for a control network has been shown and described which has many desirable  
14 attributes and advantages. The SP protocol is advantageously employed in a system  
15 controller which is adapted to be integrated with any standard network control network.  
16 The present protocol serves to transmit data relating to "system points," which convey  
17 information regarding desired system or user-defined variables in the network. The  
18 present protocol is used to transmit system point data between the network point record  
19 application (NPRA) and the various applications in the network.

20 While various embodiments of the present invention have been shown and  
21 described, it should be understood that other modifications, substitutions and  
22 alternatives are apparent to one of ordinary skill in the art. Such modifications,  
23 substitutions and alternatives can be made without departing from the spirit and scope  
24 of the invention, which should be determined from the appended claims. Various  
25 features of the invention are set forth in the appended claims